

UNIQ[®] FOAM 130 S

Solution of non-silicone defoaming polymers



UNIQ[®] FOAM 130 S is very strong defoamer based on acrylic polymer (polyvinyl ether), showing superior de-aerating effects. Suitable for all solvent based paints, to be used in various thermo-setting- and air-drying paints. Applications include architectural paints, floor coats, heavy duty paints, auto-refinishes, coil coatings and car OEM.

Special Features

- Strong defoamer
- Suitable for pigment systems
- Suitable for high viscosity and high solid coating systems
- Does not interfere intercoat adhesion
- Silicone-free
- Heat stable

Application

Architectural coatings	■
Wood and furniture coatings	■
Automotive and refinish coatings	■
Can/coil coatings	■
Industrial coatings	■

highly recommended ■

recommended □

Product Specification

Density 20°C	0.9 g/cm ³
Color	Max. 1
Appearance	Slight yellowish clear liquid

Addition levels

- Based on total formulation: 0.1 – 1.0 %

Due to its strong incompatibility, the influence upon the transparency of clear systems or other surface defects must be evaluated.

Packaging

- 25 kg
- 170 kg

Shelf life

UNIQ[®] FOAM 130 S should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 3 years from the date of manufacture.