UNIQ®LIGHT 923



Hindered Amine Light Stabilizer

General **UNIQ ELIGHT 923** is a new liquid hinder amine light stabilizer especially developed for coatings. It is based on an aminoether function which prevents possible interactions with acidic paint ingredients such as catalysts. The efficiency of **UNIQ ELIGHT 923** provides significantly extended life time to coatings by minimizing paint defects such as cracking and loss of gloss.

The performance of UNIQ®LIGHT 923 can be significantly improved when used in combination with a UV absorbers such as UNIQ®LIGHT 930 and UNIQ®LIGHT 984. These synergistic combinations give coatings superior protection against gloss reduction, cracking, blistering, delamination and colour change.

Possible interactions of UNIQ *LIGHT 923 with paint ingredients such as acid catalysts should be carefully evaluated.

Special Features

- Liquid
- Suitable for solvent-, water based and UV coatings
- Suitable for clear and pigmented coatings
- Minimize paint defects like crack and loss of gloss

Application

Architectural coatings	
Wood and furniture coatings	
Automotive and refinish coatings	
Can/coil coatings	
Protective coatings	

highly recommended ■ recommended □

Product Specification

Viscosity Density 20°C Color 3000 mPas 0.97 g/cm³ Light yellowish liquid

Packing

- 25 kg
- 190 kg

Addition levels

OEM/Refinish coatings	1.0 - 3.0%
Industrial coatings	0.5 – 2.0 %

Shelf life

UNIQ **LIGHT 923 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 2 years from the date of manufacture.

UNIQCHEM (UK) CO., LTD

www.uniqchem.com Info@uniqchem.com