

UNIQ[®]FOAM 238 S

Silicone defoamer Suitable for clear coating applications



UNID[®]**FDAM 238 S** is an air release agent to prevent foam and bubbles during the manufacture and application clear coatings for wood- and car refinish applications based on polyurethane resins. The product offers a very high clarity and will not cause haziness in the dry film.

Special Features

- Highly recommended for high gloss clear coating
- Excellent compatibility
- Effect to eliminate foam and pinholes from production and application
- High transparency
- Doesn't cause haziness

Application		
	Architectural coatings	
	Wood and furniture coatings	
	Automotive and refinish coatings	
	Can/coil coatings	
	Industrial coatings	

■ highly recommended recommended

Product Specification

Density 20 °C Refractive index Appearance 0.88 g/cm³ 1.490 Clear colorless liquid

Packaging

- 25 kg
- 170 kg

Addition levels

Protective coatings

• Based on total formulation: 0.1-0.7 % Added end of the preparation.

Shelf life

LINID[®]**FDAM 238 S** should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture.

UNIQCHEM (UK) CO., LTD

www.uniqchem.com Info@uniqchem.com

Regional headquarters

 UNIQ®FOAM, UNIQ®FLOW, UNIQ®W ET, UNIQ®SPERSE, UNIQ®LIGHT, UNIQ®COLOR, UNIQ®MICA, UNIQ®CURE, UNIQ®JET

 This information is given to the best of our knowledge. Because of the multitude of formulations, production and application

 conditions, all the above mentioned statements have to be adjusted to the circumstances of the processor.

 No liabilities, including those for patent rights, can be derived from this fact for individual cases.

 This datasheets replaces all previous issues – Printed in UK

 © Copyright UNIQCHEM (UK) CO., LTD.

 Asia:
 UNIQCHEM (Shanghai Co., Ltd.

 Tel: +86 21 5433 6480
 asia@uniqchem.com

 EMEA:
 UNIQCHEM GmbH

 Tel: +49 5821 853 7428
 au@uniqchem.com