UNIQ[®]FOAM 290 W



Water based silicone defoamer



LNID[®]**FDAM 290 W** is a strong defoamer based on organic silicon, this product can be used for grinding and spraying conditions. Working well against micro-foam, therefore also well suited for self-leveling water based epoxy flooring systems.

Special Features

- Water based and solvent free application
- Strong defoamer for grinding and after grinding
- Excellent defoaming and good compatibility
- Long term persistent

Application

highly recommended ■ recommended □

Product Specification

Density 20 °C Appearance 1.01 g/cm³ Clear liquid

Packaging

- 25 kg
- 190 kg

Addition levels

• Based on total formulation: 0.1-1.0 %

Shelf life

LINIQ[®]**FOAM 290 W** should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 2 years from the date of manufacture. At low temperature the product may become turbid, this will not affect the product performances.

UNIQCHEM (UK) CO., LTD

www.uniqchem.com Info@uniqchem.com

Regional headquarters

 UNIQ®FOAM, UNIQ®FLOW, UNIQ®W ET, UNIQ®SPERSE, UNIQ®LIGHT, UNIQ®COLOR, UNIQ®MICA, UNIQ®CURE, UNIQ®JET

 This information is given to the best of our knowledge. Because of the multitude of formulations, production and application

 conditions, all the above mentioned statements have to be adjusted to the circumstances of the processor.

 No liabilities, including those for patent rights, can be derived from this fact for individual cases.

 This datasheets replaces all previous issues – Printed in UK

 © Copyright UNIQCHEM (UK) CO., LTD.

 Asia:
 UNIQCHEM (Shanghai Co., Ltd.

 Tel: +86 21 5433 6480
 asia@uniqchem.com

 EMEA:
 UNIQCHEM GmbH

 Tel: +49 5821 853 7428
 au@uniqchem.com