

# UNIQ<sup>®</sup> LIGHT 992

Hindered Amine Light Stabilizer

General UNIQ<sup>®</sup> LIGHT 992 is a liquid hinder amine light stabilizer especially developed for coatings. It is an almost pure mixture of the two active ingredients. It is this combination that keeps the product liquid, unlike the pure diester which tends to solidify, even at room temperature. The efficiency of UNIQ<sup>®</sup> LIGHT 992 provides significantly extended life time to coatings by minimizing paint defects such as cracking and loss of gloss.

The performance of UNIQ<sup>®</sup> LIGHT 992 can be significantly improved when used in combination with a UV absorbers such as UNIQ<sup>®</sup> LIGHT 930 and UNIQ<sup>®</sup> LIGHT 984. These synergistic combinations give coatings superior protection against gloss reduction, cracking, blistering, delamination and colour change.

Possible interactions of UNIQ<sup>®</sup> LIGHT 992 with paint ingredients such as acid catalysts should be carefully evaluated.

## Special Features

- Liquid
- Suitable for solvent-, water based and UV coatings
- Suitable for clear and pigmented coatings
- Minimize paint defects like crack and loss of gloss

## Application

Architectural coatings	<input type="checkbox"/>
Wood and furniture coatings	<input checked="" type="checkbox"/>
Automotive and refinish coatings	<input checked="" type="checkbox"/>
Can/coil coatings	<input checked="" type="checkbox"/>
Protective coatings	<input checked="" type="checkbox"/>

highly recommended

recommended

## Product Specification

Viscosity	400 mPas
Color	Light yellowish liquid

## Addition levels

- OEM/Refinish coatings 1.0 – 3.0 %
- Industrial coatings 0.5 – 2.0 %
- UV coatings 0.5 – 3.0 %

## Packaging

- 25 kg
- 190 kg

## Shelf life

UNIQ<sup>®</sup> LIGHT 992 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 3 years from the date of manufacture.